

LAMPS LEGISLATION



REGULATION R48 ECE

Function	Obligatory	Optional	Remarks
Front Position	2	-	-
Rear Tail	2	2*	*M2, M3 cat. Without clearance light
A1 - Front Turn Signal	2	-	Distance to dipped beam light: 1>40mm.; 1a>20-<40mm.; 1b<20mm.
A2 - Rear Turn Signal	2	2*	*M2 and M3 cat.
A5 - Side Turn Signal	2	Minimum	Vehicle length < 6 meters
A6 - Side Turn Signal	2	Minimum	Vehicle length < 6 meters
S1 - Stop	2	2*	*Except when S3 cat. Lights are attached
S3 - Stop	-	1	Obligatory vehicles M1 cat.
R - Reversing	2	2	1 Obligatory + 1 Optional for vehicles < 6 meters
Rear Fog	1	1	>100 mm of Stop Light
Front and Rear Clearance Light	2/2	2/2	Obligatory for vehicles >2.1 meters Optional for vehicles 1.8 and 2.1 meters
Reflex Reflector	2	Par No.	-
Side Marker - Reflex Reflector	According to length of vehicle min. 1 at least one in the middle third	-	Obligatory for vehicles > 6 meters length Optional for vehicles < 6 meters length
DRL Day Running Lamp	2	-	-

